

F1069FD* Washers



MODEL NUMBER

NeveRust™ Stainless Steel Drum	
Drum volume	ℓ
Capacity	kg
Max Capacity	kg
Spin speed (max. rpm)	
G-factor	
Water Consumption	ℓ
Modified Energy Factor	
Water Factor (ℓ per cyc)	Min
Water Factor (ℓ per cyc)	Max
Inverter Direct Drive Motor	

DETERGENT DISPENSER

3 Compartment Dispenser	
Payment System	

CONTROL

Intelligent Electronic Controls	
Plumbing	

WASH PROGRAMS

Whites(Hot)	
Colors(Warm)	
Delicates(Cold)	
Permanent Press(Warm)	
Super Wash Added(Option)	
Noise Level (Sound Power)	

DIMENSIONS, WEIGHT

External dimensions WDXH	mm.
Weight (Net / Gross)	kg
Suitable for stacking	

EXTERNAL FINISH

Top Plate	
Transparent Glass Window Door	
Door Rim	
Colors	
Cabinet	
Control Panel	
Control Plate	
Window	
Window assembly	
Programme durations in minutes(Default)	

CONVENIENCE FEATURES

End of Cycle Beeper	
Door Lock Display	
Self Diagnosis	
Auto Balancing	
Auto Sud Removal	
Forced Drain System	
Remaining Time Display / Status Indicator	
Leveling Legs	
LoDecibel™ Quiet Operation	
Meter Case Cover Open Sensing	
Coin Box Open Sensing	

CONTAINER STUFFING

20 ft. Container	
40 ft. Standard Container	

F1069FD*

•
102.6
10kg
15kg
1150
413
50
2.52
42.3
56.4
•
•
•
Forced Drain System
•
•
•
•
•
Lower than 64 dB
686 X 767 X 982
87kg/ 94kg
•
Painted Steel
•
Stainless Steel
White
Painted Steel
Steel
Silk Screen
Dual Insert Molding
Vibration Welding
37 min
•
•
•
•
•
•
•
•
•
4 Adjustable
•
•
•
42
90